



# IPATOP LEVELALL® PRIMER

Self-Leveling Underlayment Primer

## IPATOP LEVELALL PRIMER

– Product Data Sheet

Self-Leveling Underlayment Primer

Description:

**IPA LEVELALL Primer** is a solvent-free copolymer liquid that improves bond to substrates when applying IPA Systems **LEVELALL® Underlayment**. It eliminates dusting of cement, prevents formation of air bubbles and promotes integrated bonding. It is non-toxic, non-flammable and non-explosive.

Uses:

Use as primer with IPA Systems **LEVELALL® Underlayment**.

### TECHNICAL DATA

Shelf Life: One year in unopened container.

Color: Milky white.

Coverage:

Normal concrete floors — 200 ft<sup>2</sup> per gallon (18.6 m<sup>2</sup> per 3.8 L).

Porous or poor concrete surface — 100 ft<sup>2</sup> per gallon (9.3 m<sup>2</sup> per 3.8 L).

Wood floors — 150 ft<sup>2</sup> per gallon (13.9 m<sup>2</sup> per 3.8 L).

Packaging:

LEVELALL Primer is available in five gallon pails (18.9 L) and cases of one gallon jugs (3.8 L).

### INSTALLATION

Surface Preparation:

All surfaces to be primed must be cleaned of any film, scale, loose material, oils, grease, old paint, curing compound and any other substance which might prevent bonding of the primer to the floor. The floor should be dry and not in hot direct sunlight. Hard surface floors such as ceramic tile, steel troweled concrete or terrazzo should be sanded, shot-blasted, scarified or otherwise roughened to aid bonding.

Application:

Apply evenly with a roller, broom or spray equipment and allow material to penetrate the floor and dry. Primer can be used up to 12 hours prior to application of underlayment. After 12 hours material should be dampened with water. Porous surfaces may require two coats. Brush off puddles. Do not leave bare spots.

Drying Time:

Approximately 90 minutes.

IPA SYSTEMS, INC.  
QUALITY PRODUCTS FOR THE  
CONCRETE/MASONRY REPAIR  
INDUSTRY

2745 North Amber Street  
Philadelphia, PA. 19134

Phone: 800-523-3834

Fax: 215-425-6234

info@ipasystems.com

Visit Our Website!  
www.ipasystems.com

## LEVELALL Primer Product Data Sheet Page 2 of 2

### Limitations:

Floor should be dry and not in hot direct sunlight. Protect from freezing and store out of direct sunlight. Do not install **LEVELALL Primer** or **LEVELALL** unless substrate and ambient temperatures are at least 40°F (4.4°C) and rising for the next 48 hours.

### **HAZARD WARNING:**

Product contains small amounts of formaldehyde and vinyl acetate which have been shown to cause cancer in animals. There should be minimal risk when used with adequate ventilation.

### **WARRANTY**

This product is warranted and guaranteed to be of good quality. Manufacturer, as its sole and exclusive liability hereunder, will replace material if proved defective. THIS WARRANTY AND GUARANTEE ARE EXPRESSLY IN LIEU OF ALL OTHERS, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND MAY NOT BE EXTENDED BY REPRESENTATIVES OR ANY PERSONS, WRITTEN SALES INFORMATION, OR DRAWINGS IN ANY MANNER WHATSOEVER.

While the manufacturer recommends uses for the product based on tests believed reliable, no warranties, express or implied, or guarantee can be given as to particular methods of use or application, nor can performance be warranted, expressly or impliedly, or guaranteed under special conditions. Distributors, salespersons or company representatives are NOT authorized to extend or vary any warranties or guarantees beyond those outlined herein nor may the manufacturer's or seller's limitation of liability be waived or altered in any manner whatsoever.